

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau




(43) International Publication Date  
8 April 2004 (08.04.2004)

PCT

(10) International Publication Number  
WO 2004/030294 A1

- (51) International Patent Classification<sup>7</sup>: H04L 12/56
- (21) International Application Number: PCT/KR2003/002001
- (22) International Filing Date: 30 September 2003 (30.09.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 02 1 44083.2 30 September 2002 (30.09.2002) CN
- (71) Applicants (for all designated States except US): SAM-SUNG ELECTRONICS CO., LTD. [KR/KR]; 416, Mae-tan-dong, Yeongtong-gu, Suwon-si, Gyeonggi-do 442-742 (KR). BEIJING SAMSUNG TELECOM R & D CENTER [CN/CN]; 4F Science and Technology Tower, No.11 Zhongguancun Nan Lu, Haidian District, Beijing 100081 (CN).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): ZHU, Yanmin [CN/CN]; 4F Science and Technology Tower, No.11 Zhongguancun Nan Lu, Haidian District, Beijing 100081 (CN).
- (74) Agent: LEE, Keon-Joo; Mihwa Bldg., 110-2, Myongryun-dong 4-ga, Chongro-gu, Seoul 110-524 (KR).
- (81) Designated States (national): JP, KR, US.
- (84) Designated States (regional): European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR).
- Published:  
— with international search report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: CIPHERING KEY MANAGEMENT AND DISTRIBUTION IN MBMS



(57) Abstract: A method for key management and assignment in MBMS service, the method includes following steps: the group key locates in the root node on the highest layer, which only has child nodes and doesn't have parent nodes; private keys corresponding to users locate in leaf nodes; the described intermediate node that owns both one parent node and one or more child nodes holds its own key. This invention deploys the method of combining point-to-point mode and point-to-multipoint mode during the process of key update; compared with the key update method only deploying point-to-point mode, this method can reduce the times necessary for information transmission, reduce the system load as well as the time needed for one key update process. Compared with the key update method only deploying point-to-multipoint mode, this solves the security problem of key exposure.